



POST SECTIONS

LEFT CROSSBAR SECTION

RIGHT CROSSBAR SECTION

UPRIGHT SECTION






(21' x 7') - Two section crossbar.



SPARE PARTS TEL: 0114 24 34 200






F










FITTING THE NET FIXINGS



INSERT NET FIXINGS INTO HOLES ON REAR A LOCKING PIN IS LOCATED ON THE TOP OF THE NET FIXING DO NOT THROW THE

PUSH LOCKING PIN FULLY INTO THE NET FIXING, THIS WILL SECURE IT IN PLACE. REMOVING THE NET FIXING

THE LOCKING PIN CAN BE PUSHED COMPLETELY THROUGH THE FIXING BY USING A ROD LESS THAN 4MM IN DIAMETER (SUCH AS A BLUNT NAIL). WHEN PUSHED FULLY THROUGH THE PIN WILL DROP INSIDE THE POST AND ALLOW THE FIXING TO BE PULLED **OUT. SAVE THE LOCKING PIN IF FIXINGS ARE TO BE REUSED.**



A HAMMER OR SOLID OBJECT. TAP THE CORNER SECTIONS WITH A RUBBER MALLET. MAKE DISASSEMBLY.



DO NOT SWING ON CROSSBARS

CROSSBARS WILL NOT BE REPLACED WITHIN THE GUARANTEE PERIOD IF BROKEN BY SWINGING OR CLIMBING OR ANY OTHER MISUSE.

NOTE: PORTABLE ALUMINIUM GOALS ARE LIGHTWEIGHT AND THEREFORE THE CROSSBAR WILL DEFORM IF 1800 NEWTONS IS APPLIED AS IN BSEN748, MUCH HEAVIER 100MM X 115mm AND 80MM X 80MM DIAMETER ALUMINIUM TUBE ARE AVAILABLE WHICH CONFORM FULLY TO THE BS EN 748



WARNING: CHECK THE

UNDERGROUND SERVICES

RESPONSIBILITY FOR ANY

IMPACT TO HELP PREVENT

TAP SIDES OF SPIKE WITH

BEFORE USING THE GROUND

SPIKES AND PEGS. WE TAKE NO

DAMAGE OR INJURY CAUSED IN

THIS MANNER, OUR GROUND

ANCHOR SYSTEM IS DESIGNED

SERIOUS INJURY. TO LOOSEN

HAMMER BEFORE EXTRACTING

GROUND SOCKETS FILLED WITH

YOU MAY NEED TO INSTALL

SAND IF USED IN THE SAME

TO GIVE SLIGHTLY UNDER HEAVY

POSITION OF ANY

NEVER ALLOW THE GOAL TO

STANCHIONS ARE FITTED. THIS

MAY CAUSE THEM TO BREAK.

WHEN LIFTING OR LOWERING

GOAL ENSURE AREA IS CLEAR OF

FALL FORWARDS WHILE THE

STRESS

POINTS

GROUND ANCHORS - NOTE: ALWAYS ENSURE ALIGNMENT OF GROUND SPIKES IS CORRECT TO ALLOW UPRIGHTS TO EASILY SLIDE OVER TOP OF SPIKE. DO NOT USE FRONT GROUND SPIKES IF THEY BECOME MISSHAPEN OR DAMAGED AS THIS COULD CAUSE DAMAGE TO THE BASE OF LIPRIGHT

WE ADVISE ADULT SUPERVISION DURING ASSEMBLY AND USE.

TELEPHONE OUR GOAL-LINE 0114 243 4200 DAMAGED COMPONENTS REQUESTED UNDER GUARANTEE MUST BE RETURNED FOR

IF NET HOOKS DO NOT STAY IN POSITION WHEN PIN IS INSERTED, THE PIN MAY HAVE BECOME

WORN, AS A TEMPORARY MEASURE YOU CAN WRAP TAPE AROUND THE MIDDLE OF THE PIN

LOOSEN SOIL WITH A STEEL POLE AND MOISTEN WITH SOME WATER BEFORE INSERTING THE

NOTE: WHEN USING A BAG PLEASE PACK THE GOAL SECTIONS CAREFULLY INTO THE BAG. THE

COMPONENTS ARE DESIGNED TO FIT INTO THE BAG EFFICIENTLY AND THEREFORE. DO NOT

BAG MAINTENANCE - SPONGE BAG DOWN WITH HOT SOAPY WATER. ZIP WILL RUN EASIER IF

UNDER ANY CIRCUMSTANCE THROW THE COMPONENTS INTO THE BAG AND THEN FORCE THE

HARD GROUND CONDITIONS: TO PREVENT DAMAGE TO GOAL OR IT'S COMPONENTS.

OBSERVE AND FOLLOW WARNING LABELS ATTACHED TO GOAL.

SPARE PARTS AND REPLACEMENT NETS ARE READILY AVAILABLE

AND THIS SHOULD HELP TIGHTEN THE PIN INSIDE THE HOOK.

ZIP TO CLOSE AS THIS WILL BREAK THE ZIP FASTENER.

YOU RUB BOTH SIDES OF THE ZIP TRACK WITH CANDLE WAX

DO NOT USE GOALS WITH ANY DAMAGED OR MISSING COMPONENTS.

CONTAINED IN THIS DOCUMENT, MAY INVALIDATE YOUR GUARANTEE.

INSPECTION. FAILURE TO FOLLOW THE WARNINGS, FITTING INSTRUCTIONS

LOCKING PINS AWAY

NEVER STRIKE THE POSTS WITH ALWAYS PRISE APART OR LIGHTLY SURE POSTS AND CORNERS ARE IN LINE DURING ASSEMBLE AND

STANDARD 20cm **NET PEG** LONGER 30cm PEG FOR SOFTER GROUND

WARNING: WE RECOMMEND A RISK ASSESSMENT OF SOIL CONDITIONS, EG. FOR SOFT, VERY WET OR SANDY GROUND WE STRONGLY RECOMMEND OUR LONGER 300MM NET PEG IS USED (AVAILABLE SEPARATELY). FREESTANDING GOALS WITH COUNTER BALANCE WEIGHTS MAY BE MORE SUITABLE FOR EXTREME GROUND CONDITIONS.



REAR GROUND ANCHORS Once fitted Rear Ground Anchor can stay connected to Back Stanchion Tube for storage.

CLEANING A

GROUND ANCHOR.

CARE & MAINTENANCE

AT THE END OF THE SEASON NETS CAN BE TIED INTO A BUNDLE PUT INTO AN OLD PILLOW CASE, AND TIE SHUT (NOT TO DAMAGE WASHING MACHINE) AND WASHED IN A COOL WASH WITH NORMAL WASHING POWDER. THE GOAL FRAME CAN BE WASHED WITH HOT SOAPY WATER. ANY SCUFF MARKS CAN BE RUBBED OFF WITH A LIGHT ABRASIVE SCOURING PAD.

WARNING

THE GOAL IS DESIGNED FOR ASSOCIATION FOOTBALL (SOCCER) ONLY AND NO OTHER PURPOSE.

CHECK ALL FITTINGS ARE FULLY SECURED BEFORE USE AND CHECKED PERIODICALLY. ENSURE THAT THE UPRIGHTS AND BACK STANCHIONS ARE STRAIGHT AND PROPERLY ALIGNED BEFORE FITTING THE NET.

WHEN LIFTING OR LOWERING GOAL ENSURE AREA IS CLEAR OF BYSTANDERS TO PREVENT INJURY.

IT IS ADVISABLE IN EXTREME WINDY CONDITIONS TO DISMANTLE THE GOAL AND STORE AWAY. WHEN DISMANTLING THE GOAL ENSURE THAT ALL FITTINGS ARE PACKED AWAY AND THAT NOTHING IS LEFT ON THE PLAYING SURFACE.

DO NOT USE DAMAGED NETS.

NEVER USE GOALS WITHOUT SECURING BOLTS.

GOALS MUST NEVER BE LEFT UP OR USED UNLESS THEY ARE PROPERLY FITTED WITH GROUND SPIKES AND ANCHORS WITH NET ATTACHED AND SECURELY PEGGED DOWN.

DO NOT AT ANY TIME USE YOUR GOAL WITHOUT GROUND ANCHORS.

DO NOT CLIMB ON THE NET OR GOAL FRAME. DO NOT DROP ANY HEAVY OBJECTS ON ENDS OF TUBES.


NO LIABILITY IS ACCEPTED WHATSOEVER BY THE COMPANY IT'S EMPLOYEES OR AGENTS FOR DAMAGED LOSS OR INJURY CAUSED BY NEGLIGENCE OR MISUSE.

IT IS ADVISABLE IN ANY CONTACT SPORT TO TAKE OUT THE RELEVANT INSURANCE'S TO COVER AGAINST INJURY BOTH FROM TAKING PART, EQUIPMENT AND OTHER UNFORESEEABLE CIRCUMSTANCES

FITTING THE NET

ATTACH THE NET TO THE GOAL FRAME

SQUARE MESH NET IS CUT TO SHAPE SIMPLY THROW OVER THE FRAME AND FIT FACH FND ONTO TOP STANCHION BY SECURING ON CORNER NET FIXINGS, THEN ATTACH TO FIXINGS ALONG CROSSBAR, THEN TO UPRIGHTS.




NOTE: IF YOUR NET DOES NOT FIT THE FIRST TIME, YOU ARE FITTING IT TO THE GOAL FRAME UPSIDE DOWN I.E. THAT IS TO SAY THE NET FROM THE CROSSBAR TO THE FLOOR (A) IS LONGER THAN THE LENGTH OF THE NET TO THE BOTTOM OF THE UPRIGHT.(B)

NOTE: IF YOU SETTING YOUR GOAL(S) UP REGULARLY THEN IT IS A GOOD IDEA TO ATTACH SOME TAPE TO THE NET SO YOU CAN EASILY IDENTIFY THE TOP CORNERS. WE RECOMMEND THAT ONLY NETS WITH 100MM X 100MM MESH BE USED WITH CHILDREN TO COVER HEAD ENTRAPMENT REGULATIONS 120MM X 120MM MESH IS ACCEPTABLE FOR USE BY ADULTS.




TO AVOID DAMAGE TO NETS -DO NOT REMOVE PEGS BY PULLING FROM GROUND WITH BOTTOM OF NET. REMOVE THE PEGS AS SHOWN USING ANOTHER PEG.



WARNING: DO NOT TOUCH OVERHEAD SERVICES WITH GOALPOST SECTIONS. CHECK THE POSITION OF ANY OVERHEAD SERVICES WHEN SETTING UP OR DISMANTLING THE GOALS EG POWER LINES TELEPHONE CABELS ETC.



A HANDY 280cm GOAL **CARRY BAG TO TRANSPORT** AND STORE YOUR PORTABLE **GOAL IS AVAILABLE** SEPARATELY.



NOT SUITABLE FOR CHILDREN UNDER 36 MONTHS UNTIL ASSEMBLES DUE TO SMALL PARTS

WORLDWIDE © COPYRIGHT 2000 ITSA GOAL POSTS LTD. ALL RIGHTS RESERVED. A REGISTERED DESIGN & PATENTED PRODUCT.

PATENT REGISTRATION & TRADEMARK REFERENCE NUMBERS: 2103675 2055727 2099842 2099841 0513170 22153513 2215353A USD442851 US5316314 US335440 US1754545 AUS649244